

Mueller Co.Reliable Connections[®]**Drilling Travel**

Necessary travel to complete the cut from point of pilot drill contact on pipe.

Fitting/Size	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"
H-17055	1-9/16"	1-13/16"	2-1/4"	-	-	-
H-17056	1-9/16"	1-13/16"	2-1/4"	-	-	-
H-17125	-	-	-	-	3-27/32"	-
H-17126	-	-	-	-	3-27/32"	-
H-17155	-	-	-	3-3/8"	3-27/32"	4-3/8"
H-17156	-	-	-	3-3/8"	3-27/32"	4-3/8"
H-17160	-	-	-	3-3/8"	3-27/32"	4-3/8"
H-17161	-	-	-	-	3-27/32"	4-3/8"
H-17165	-	-	-	-	3-27/32"	-

Top & bottom of pipe are cut (two piece fitting)

www.muellergas.com



Reliable Connections[®]

Stopping Travel

Maximum downward travel of boring bar required for stop-off

Fitting/Size	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"
H-17055	3/4"	1-1/8"	1-1/2"	-	-	-
H-17056	3/4"	1-1/8"	1-1/2"	-	-	-
H-17125	-	-	-	-	1"	-
H-17126	-	-	-	-	1"	-
H-17155	-	-	-	1"	1"	1-1/4"
H-17156	-	-	-	1"	1"	1-1/4"
H-17160	-	-	-	1"	1"	1-1/4"
H-17161	-	-	-	-	1"	1-1/4"
H-17165	-	-	-	-	1"	-

One turn of feed yoke equals 1/8" of travel: Example - 7/8" = 7 turns of feed yoke